

## USB 16 Photo-Iso Input Board

**Product Code:**


AUSB16PHOTO USB 16 PHOTO ISO. INPUT BOARD

**Bus:** USB 2.0 / RS-232/422/485

**Description:** 16 photo couple input channels

Input maximum load voltage is 30V  
By jumper, you can select two range of voltage  
0 - 4.5V off and 6V - 20V on. (0 - 20V)  
0 - 16.5V off and 18 - 30V on (0 - 30V)  
PC817 photo couple chips.  
5000V isolation voltage.

16 LED correspond to input ports activation status.



**Connection:**

Easy exchange by interchangeable screw-terminals

**Features:**

For direct DIN-Rail mounting  
Also as board without  
DIN Rail adapter available

High Speed 8051  $\mu$ C Core  
USB 2.0 Function Controller  
Support USB ID 0~14 SET  
Support RS-232/422/485 Communicate  
POWER from USB OR External DC+5V 3A

**Software/Driver:**

Windows-XP Vista will use HID-interface and sample for programming,  
Linux driver and sample for programming.

**Package includes the following items:**

USB 16PHOTO Board  
USB cable  
Software and Manual CD

**Operating temperature range:** from 0 to 33C.  
**Relative humidity rage:** from 0 to 90%.  
**Size:** 200 mm x 120 mm x 55 mm



**DECISION COMPUTER INTERNATIONAL CO., LTD.**



4/F No. 31, Alley 4, Lane 36, Sec.5  
Ming-Shen East Road

Taipei, Taiwan, R.O.C.

**Phone No :** +886 2 2766-5753  
**Fax No :** +886 2 2766 5702, 2756 9591  
**E - Mail :** [decision@ms1.hinet.net](mailto:decision@ms1.hinet.net)  
[decision@decision.com.tw](mailto:decision@decision.com.tw)  
**URL :** [www.decision.com.tw](http://www.decision.com.tw)