

USB 16 Photo-Isolator I/O Board

Product Code:

AUSB16PI/O USB 16 PHOTO ISO. INPUT/OUTPUT BOARD

Bus: USB 2.0


Description: Support 16 photo couple input/output channels

Input max. load is 30V
By jumper, you can select two range of voltage
0 - 4.5V off and 6V - 20V on. (0 - 20V)
0 - 16.5V off and 18 - 30V on (0 - 30V)
PC817 photo couple chips.
5000V isolation voltage.

Output voltage : $V_{cd} = 35V$, $V_{ec} = 6V$, and max.
Collector current 50mA. (Maximaler continuous
current < 30mA.)

32 LED correspond to I/O ports activation status.

Connection:



Easy exchange by interchangeable screw-terminals

Features:

For direct DIN-Rail mounting
Also as board without
DIN Rail adapter available

High Speed 8051 μC Core
USB 2.0 Function Controller
Support USB ID 0~14 SET
Power from USB or External DC+5V/3A

Software/Driver:

Windows-XP Vista will use HID-interface and sample for programming,
Linux driver and sample for programming.

Package includes the following items:

USB 16PI/OBoard
USB cable
Software and Manual CD

Operating temperature range: from 0 to 33C.
Relative humidity range: from 0 to 90%.
Size: 250 mm x 120 mm x 55 mm



DECISION COMPUTER INTERNATIONAL CO., LTD.



4/F No. 31, Alley 4, Lane 36, Sec.5
Ming-Shen East Road

Taipei, Taiwan, R.O.C.

Phone No : +886 2 2766-5753

Fax No : +886 2 2766 5702, 2756 9591

E - Mail : decision@ms1.hinet.net
decision@decision.com.tw

URL : www.decision.com.tw