

USB 16 Relay Output Board

Product Code:

AUSB16RELAY USB 16 RELAY OUTPUT BOARD


Bus: USB 2.0 / RS-232/422/485

Description: 16 relay output channels

16 DPDT-Relays - 2 x COM/NO/NC

Max switching current: 1A
Max contact rating for relay: 220V AC / 150V DC

16 LED correspond to output ports activation status.



Connection:

Easy exchange by interchangeable screw-terminals

Features:

For direct DIN-Rail mounting
Also as board without
DIN Rail adapter available

High Speed 8051 μ C Core
USB 2.0 Function Controller
Support USB ID 0~14 SET
Support RS-232/422/485 Communicate
POWER from External DC+5V 3A

Software/Driver:

Windows-XP Vista will use HID-interface and sample for programming,
Linux driver and sample for programming.

Package includes the following items:

USB 16RELAY Board
USB cable
Software and Manual CD

Operating temperature range: from 0 to 33C.
Relative humidity range: from 0 to 90%.
Size: 250 mm x 120 mm x 55 mm



DECISION COMPUTER INTERNATIONAL CO., LTD.



4/F No. 31, Alley 4, Lane 36, Sec.5
Ming-Shen East Road

Taipei, Taiwan, R.O.C.

Phone No : +886 2 2766-5753
Fax No : +886 2 2766 5702, 2756 9591
E - Mail : decision@ms1.hinet.net
decision@decision.com.tw
URL : www.decision.com.tw