

## USB 32 Photo-Iso Input Board

### Product Code:


AUSB32PHOTO USB 32 PHOTO ISO. INPUT BOARD

**Bus:** USB 2.0 / RS-232/422/485

**Description:** 32 photocoupler input channels

Input maximum load voltage is 30V  
By jumper, you can select two range of voltage  
0 - 4.5V off and 6V - 20V on. (0 - 20V)  
0 - 16.5V off and 18 - 30V on (0 - 30V)  
PC817 photocoupler chips.  
5000V isolation voltage.

32 LED correspond to input ports activation status.



### Connection:

Easy exchange by interchangeable screw-terminals

### Features:

For direct DIN-Rail mounting  
Also as board without  
DIN Rail adapter available

High Speed 8051  $\mu$ C Core  
USB 2.0 Function Controller  
Support USB ID 0-14 SET  
Support RS-232/422/485 Communicate  
POWER from USB OR External DC+5V 3A

### Software/Driver:

Windows-XP Vista will use HID-interface and sample for programming,  
Linux driver and sample for programming.

### Package includes the following items:

USB 32PHOTO Board  
USB cable  
Software and Manual CD

**Operating temperature range:** from 0 to 33C.  
**Relative humidity range:** from 0 to 90%.  
**Size:** 250 mm x 120 mm x 55 mm



## DECISION GROUP INC.



4/F No. 31, Alley 4, Lane 36, Sec.5  
Ming-Shen East Road

Taipei, Taiwan, R.O.C.

**Phone No :** +886 2 2766-5753  
**Fax No :** +886 2 2766 5702, 2756 9591  
**E - Mail :** [decision@ms1.hinet.net](mailto:decision@ms1.hinet.net)  
[decision@decision.com.tw](mailto:decision@decision.com.tw)  
**URL :** [www.decision.com.tw](http://www.decision.com.tw)