



## USB 8 Photo-Iso / Relay Board

### Product Code:

AUSB8P/R USB 8 PHOTO ISO./ RELAY BOARD

**Bus:** USB 2.0

**Description:** 8 photocoupler input / relay output channels

Input maximum load voltage is 30V  
By jumper, you can select two range of voltage  
0 - 4.5V off and 6V - 20V on. (0 - 20V)  
0 - 16.5V off and 18 - 30V on (0 - 30V)  
PC817 photocoupler chips.  
5000V isolation voltage.  
Maximum 30V / current 500mA

8 DPDT-Relays - 2 x COM/NO/NC  
Max switching current: 1A  
Max contact rating for relay: 220V AC / 150V DC

16 bits Digital Input/Output TTL - 5V  
16 LED correspond to I/O ports activation status.



### Connection:

Easy exchange by interchangeable screw-terminals

### Features:

For direct DIN-Rail mounting  
Also as board without  
DIN Rail adapter available

High Speed 8051  $\mu$ C Core  
USB 2.0 Function Controller  
Support USB ID 0-14 SET  
POWER from External DC+5V 3A

### Software/Driver:

Windows-XP Vista will use HID-interface and sample for programming,  
Linux driver and sample for programming.

### Package includes the following items:

USB 8PR Board  
USB cable  
Software CD  
English Manual

**Operating temperature range:** from 0 to 33C.  
**Relative humidity range:** from 0 to 90%.  
**Size:** 250 mm x 120 mm x 55 mm



## DECISION GROUP INC.



4/F No. 31, Alley 4, Lane 36, Sec.5  
Ming - Shen East Road

Taipei, Taiwan, R.O.C.

**Phone No :** +886 2 2766-5753

**Fax No :** +886 2 2766 5702, 2756 9591

**E - Mail :** [decision@ms1.hinet.net](mailto:decision@ms1.hinet.net)  
[decision@decision.com.tw](mailto:decision@decision.com.tw)

**URL :** [www.decision.com.tw](http://www.decision.com.tw)